



# AMS HADEN

INSTRUMENT AND MINING SERVICES PTY LTD

PROPR HADEN INSTRUMENT SERVICES PTY LTD

## DIGI-NOISE SIGN



### FEATURES & TECHNICAL SPECS

- 110-230VoltACPowerwithBatterybackupoptions
- Continues4-20mAOutputforSCADAMonitoring
- Red/GreenVisualWarningIndication
- DigitalDisplaywith50mviewingdistance
- Dustresistant/Builtwithminingandindustrial applications in mind
- Ideal for Workshops / Underground / Lamprooms / Smelters / Plants etc.
- Adjustable alarm point

Measure Range	Range 1: 30 - 80 dB Range 2: 50 - 100 dB Range 3: 80 - 130 dB
Output	4 - 20 mA Range 1: 30 dB:7.69 mA 80 dB:13.84mA Range 2: 50dB:10.15 mA 100dB:16.3mA Range 3: 80dB:13.84mA 130 dB:20 mA
External Adjustment	94 dB Cal. VR
Power Supply	90 - 260 ACV 50 Hz/60 Hz
Operation Temperature	0 - 50 °C 32 - 122 °F
Operation Humidity	Less than 80 %RH
Accessory Included	Sound level Probe
Optional Accessories	Sound calibrator, SC-941 (94 dB) SC-942 (94 dB/114 dB)
Mounting	Din rail or Wall
Case	ABS plastic
Others	Separate probe

Tel: +27 11 475 2064 | Fax: +27 86 551 0788 | Email: info@amshaden.co.za

Postal Address: Unit B Kimbult Office park, 9 Zeiss road, Laserpark, Honeydew

www.amshaden.co.za



INNOVATING TOWARDS  
**zero**harm